



## ECF

### Quick Acting High Breaking Capacity

- 5Ø x 20 mm (0.197 x 0.787 inch)
- Ampere Rating: 63mA to 25 A
- Voltage Rating: 250V
- **Standards:** IEC Standards
- **Option:** Available Add Axial Leads

Model No. **ECF-A**

#### • Electrical Characteristics:

Rated Current	1.5 In	2.1 In	2.75 In		4 In		10 In
	MIN	MAX	MIN	MAX	MIN	MAX	MAX
63mA ~ 100mA	60	30 min	10 ms	2 sec	3 ms	300 ms	20 ms
125mA ~ 25A	60 min	30 min	10 ms	3 sec	3 ms	300 ms	20 ms



## ECT

### Time-Lag High Breaking Capacity

- 5Øx20 mm (0.197x0.787 inch)
- Ampere Rating: 63mA to 25 A
- Voltage Rating: 250V
- **Standards:** IEC Standards
- **Option:** Available Add Axial Leads

Model No. **ECT-A**

#### • Electrical Characteristics:

Rated Current	1.5 In	2.1 In	2.75 In		4 In		10 In	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
63mA ~ 3.15A	60 min	30 min	200 ms	10 sec	40 ms	3 sec	10 ms	300 ms
4A ~ 25A	60 min	30 min	600 ms	10 sec	150 ms	3 sec	20 ms	300 ms



## UCF

### Quick Acting High Breaking Capacity

- 6.3Øx32 mm (1/4x1-1/4 inch)
- Ampere Rating: 100mA to 35 A
- Voltage Rating: 500V
- **Standards:** IEC Standards
- **Option:** Available Add Axial Leads

Model No. **UCF-A**

#### • Electrical Characteristics:

Rated Current	1.5 In	2.1 In	4 In	10 In
	Min	Max	Max	Max
100mA ~ 35A	60 min	30 min	300ms	20ms



## UCT

### Time-Lag High Breaking Capacity

- 6.3Øx32 mm (1/4x1-1/4 inch)
- Ampere Rating: 100mA to 25 A
- Voltage Rating: 500V
- **Standards:** IEC Standards
- **Option:** Available Add Axial Leads

Model No. **UCT-A**

#### • Electrical Characteristics:

Rated Current	1.5 In	2.1 In	2.75 In		4 In		10 In	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
50mA ~ 25A	60 min	30 min	600 ms	10 sec	200 ms	4 sec	50 ms	450 ms



## GGU

### Normal Blow Glass Tube Fuses

- 10.3Øx38.1 mm (13/32x1-1/2 inch)
- Ampere Rating: 500mA to 80 A
- Voltage Rating: 250V and less
- **Electrical Characteristics:**  
135% - 1 Hour, **Maximum**, A≤30  
150% - 1 Hour, **Maximum**, A>30  
200% - 30 Seconds, **Maximum**
- Caps: Golden Finish For High Performance
- Equivalent AGU and 5AG Fuse

#### • Approvals:



## AUB

### Normal Blow Ceramic Tube Fuses

- 10.3Øx38.1 mm (13/32x1-1/2 inch)
- Ampere Rating: 500mA to 80A
- Voltage Rating: 600V and less
- **Electrical Characteristics:**  
135% - 1 Hour, **Maximum**  
200% - 120 Seconds, **Maximum**
- Caps: Golden Finish For High Performance
- Standards: UL, CSA 30A and less